


SEE NOTE NO. 2



2½" A.C. ON NATIVE SOIL
COMPACTED TO 90% RELATIVE
COMPACTION

NOTES:

1. Cross slopes and longitudinal slopes shall be as directed by the Engineer and in such a manner as to provide for adequate drainage and smooth riding characteristics. Cross slope shall not be less than 2% nor more than 5%.
2. The minimum width of the bikeway shall be 8' for a two-way bikeway and 5' for a one-way bikeway unless otherwise shown on plans.
3. Location and alignment of bikeway shall be as shown on plans.
4. All tree limbs overhanging the bikeway and less than 8' above the bikeway shall be trimmed back as directed by the Engineer. Minimum lateral clearance to obstructions shall be 3'.
5. Asphaltic Concrete shall be Class D2-AR-4000. 
6. Prior to placing asphaltic concrete, apply an approved herbicide, rate of application per manufacturers recommendations.

APPROVED  DATE 7/14/78
PUBLIC WORKS DIRECTOR - R.C.E. 18793

CITY OF RIVERSIDE
PUBLIC WORKS DEPT. - ENGINEERING DIV.

 CHANGED CLASS NAME  7-7-82

CLASS I BIKEWAY

STANDARD DRAWING NO.

111

MARK REVISIONS APPR. DATE